

SPECIFICATION OF PRODUCT

For Lithium-ion Battery Pack

60V 40Ah(2400Wh)

Mail : sales@dnkpower.com

Tel: +86 755 36827358

Mob:+86 189 4877 2006

60V 40AH (2400Wh)

Lithium-ion Battery Pack Specification

Issue by:DNK Power Technology Co., Ltd

Designer : Eric Liu

Verify: 10

Rev: V0.1

Date: 2021-10-07

Copyright : Copying or distribution of this specification, or files associated with this specification, is strictly prohibited.

Confidential

CONTENT

- 1、 Product Introduction
- 2、 Characteristic Curve
- 3、 BMS
- 4、 Cautions
- 5、 Product Liability

1、 Product Introduction


1.1 Specifications

NO	Item	SPEC	Remark
1	Rated Capacity	40AH	
2	Rated Voltage	DC60	
3	Rated Energy	2400wh	
4	Operating Voltage	44.8V~67.2V	2.8V~4.2V
5	Max. Charge Current	20A	
6	Max. Discharge Current	40A	
7	Peak Current	120A	
8	Ip Grade	IP54	
9	Discharge Temp	-10°C~55°C	
10	Charge Temp	0°C~55°C	
11	Dimension	L230*W180*H300 (mm)	
12	Weight	18Kg	
13	Internal Resistance	≤60mΩ	
14	Cycle Life	2000	25°C
15	Case Material	Metal	






1、 Product introduction

1.2 Model




1、Product introduction

1.3 Interface Command

Item	SPEC	Interface	Refer
CHARGE	14AWG silicone wire 300mm	XT60-F	
DISCHARGE	"N"+, "L"-	"Goods"	
LCD	Display: electric quantity, voltage	Green screen	

2、Characteristic Curve



3、 BMS

BMS Description

NO	Item	MIN	MAX	Type	Unit
1	Operating Voltage	44.8	67.2	/	V
2	Continuous Charging Current	1	20	/	A
3	Continuous Discharging Current	1	40	/	A
4	Discharging Over Current	110	130	/	A
5	Operating Temp	-10	70	/	°C
6	Operating Humidit	10	85	/	%
7	Internal Resistance	<10			mΩ
8	Normal Operating Consumption	<30			mA
9	Static Total Consumption		100	50	uA

4、Cautions

- (1) Do not immerse the battery in water, and keep the battery in a cool dry surrounding if it stands by.
- (2) Do not use or leave the battery at high temperature as fire or heater. Otherwise, it can overheat or fire or its performance will be degenerate and its service life will be decreased.
- (3) Do not reverse the position and negative terminals.
- (4) Do not connect the battery electrodes to an electrical outlet.
- (5) Do not short circuit. Otherwise it will cause serious damage of the battery.
- (6) Do not transport or store the battery together with metal objects such as hairpins, necklaces, etc.
- (7) Do not use the battery in a location where static electricity and magnetic field is great, otherwise, the safety devices may be damaged, causing hidden trouble of safety. Turn off the switch on its base.
- (8) Please use special lithium charger.
- (9) It should be noted that the cell would be possible to be at a over-discharged state by its self-discharge characteristics in case the cell is not used for long time. In order to prevent over-discharging, the cell shall be charged periodically to maintain about 64V(Recommended 3 months one cycle). Over-discharging may causes loss of cell performance, characteristics, or battery functions.
- (10) Do not disassemble battery.

5、 Product Liability

Company is not responsible for the incident caused by not obeying the specifications. Before using the battery, you should read the specifications, usage instruction and some attentions carefully to learn its application method and areas. If the phenomenon such as error using method or wrong circuit connection, or input power data, working index are inconsistent with the specifications, cause damage to product, load and its accessories, we are not responsible for it.

The company reserves the right to change the contents of this specification without prior notice. All copyrights reserved.