

**1 YEAR WARRANTY**


**DNK**

3.7V DNK272031 150mAh LiPo Battery Pack with PCM. This datasheet describes the properties which is manufactured by DNK POWER Co. Ltd.- China.

**Battery Dimension Pictures**



Item	Parameter (mm)
T	2.7
W	20
M	10
L	31.0
L <sub>1</sub>	33.0
BL	33.0 ± 1
CL	100



**Electrical Data**

Part Number	LP 272031
Nominal Voltage	3.7V
Nominal Capacity	150 mAh
Internal Impedance	<60mΩ
Charge Voltage	4.2V
Recommended Charge Current	0.2C
Allowed Max Charge Current	0.5C
Output Voltage Range	4.2 - 2.5V
Recommend Discharge Current	0.2C
Max Continuous Discharge Current	1C
Pulse Discharge Current	3C(10mS)
Discharge Cut-off Voltage	2.5 ± 0.05V
Cycle Life to 80% Health	500(0.2C, 25°C)

**Environmental Data**

Charging Temperature Range	0 - 45° C
Discharge Temperature Range	-20 - 60° C
Storage Period 1 Week	-20 - 45° C
Storage Period 1 Month	-10 - 45° C
Storage Period 6 Months	0 - 35° C

**Battery Protection**

Over Charge	4.275 ± 50mV
Over Discharge	2.5V ± 50mV
Over Current	3A to 5A
Short Circuit	Yes

**Mechanical Data**

Dimension(L <sub>1</sub> +W*T)	33.0 x 20 x 2.7 mm
Weight	≤5 g
Battery Terminals	WC/FL*

\*WC=With Connector FL=Flying Leads Specifications are subject to change without notice



**ANNOUNCEMENTS**

- Have a fire extinguisher near the LiPo battery charging area and/or a large bucket of dry sand.
- Do not fully discharge your LiPo battery pack. Discharging a LiPo beyond it's critical minimum voltage (often 3.0v) can cause damage to the battery.
- Ensure that charging leads are connected correctly. Reverse charging can lead to cell damage, fire or explosion.

**CONTACT INFO**

Mail: sales@dnkpower.com  
 Tel:+86 755 36827358  
 Mob:+86 189 4877 2006  
 Hour of operation: 9:00am-6:00pm, Mon. to Fri.  
 Learn More on: <https://www.dnkpower.com/>