3.7V DNK386784 3420mAh LiPo Battery Pack with PCM. This datasheet describes the properties which is manufactured by DNK POWER Co. Ltd.- China.

Electrical Data

Part Number	LP 386784
Nominal Voltage	3.7V
Nominal Capacity	3420 mAh
Internal Impedance	＜60mΩ
Charge Voltage	4.2V
Recommended Charge Current	0.2C
Allowed Max Charge Current	0.5C
Output Voltage Range	4.2 - 2.5V
Recommend Discharge Current	0.2C
Max Continuous Discharge Current	1C
Pulse Discharge Current	3C(10mS)
Discharge Cut-off Voltage	2.5±0.05V
Cycle Life to 80% Health	500(0.2C, 25℃

Environmental Data

Charging Temperature Range	0 – 45° C
Discharge Temperature Range	-20 – 60° C
Storage Period 1 Week	-20 – 45° C
Storage Period 1 Month	-10 – 45° C
Storage Period 6 Months	0 – 35° C

Battery Protection

Over Charge	4.275 ± 50mV
Over Discharge	2.5V ± 50mV
Over Current	3A to 5A
Short Circuit	Yes

Mechanical Data

Dimension(L_1*W*T)	86 x 67 x 3.8 mm
Weight	appr 57 g
Battery Terminals	WC/FL*

*WC=With Connector FL=Flying Leads

Battery Dimension Pictures



Item	Parameter (mm)
T	3.8
W	67
M	10
L	84
L_1	86
BL	86 ± 1
CL	100



1 YEAR WARRANTY

DNK





ANNOUNCEMENTS

- A 1s or 1 cell LiPo battery has a nominal voltage of 3.7V. When fully charged it has a maximum voltage of 4.2V. When fully discharged, it should never go below 3.0v without risking cell damage.
- Be aware that many of the more expensive LiPo chargers will automatically detect the cell count of the battery being charged; cheaper chargers will require a manual setting.
- Never store batteries inside of an automobile.

CONTACT INFO

Mail: sales@dnkpower.com

Tel:+86 755 36827358 Hour of operation: 9:00am-6:00pm, Mon. to Fri.

Mob:+86 189 4877 2006 Learn More on: https://www.dnkpower.com/

Specifications are subject to change without notice.