3.7V DNK395890 3870mAh LiPo Battery Pack with PCM. This datasheet describes the properties which is manufactured by DNK POWER Co. Ltd.- China.

Electrical Data

Part Number	LP 395890
Nominal Voltage	3.7V
Nominal Capacity	3870 mAh
Internal Impedance	＜60mΩ
Charge Voltage	4.2V
Recommended Charge Current	0.2C
Allowed Max Charge Current	0.5C
Output Voltage Range	4.2 - 2.5V
Recommend Discharge Current	0.2C
Max Continuous Discharge Current	1C
Pulse Discharge Current	3C(10mS)
Discharge Cut-off Voltage	2.5±0.05V
Cycle Life to 80% Health	500(0.2C, 25℃

Environmental Data

Charging Temperature Range	0 – 45° C
Discharge Temperature Range	-20 – 60° C
Storage Period 1 Week	-20 – 45° C
Storage Period 1 Month	-10 – 45° C
Storage Period 6 Months	0 – 35° C

Battery Protection

Over Charge	4.275 ± 50mV
Over Discharge	2.5V ± 50mV
Over Current	3A to 5A
Short Circuit	Yes

Mechanical Data

Dimension(L_1*W*T)	92 x 58 x 3.9 mm
Weight	appr 64.5 g
Battery Terminals	WC/FL*

*WC=With Connector FL=Flying Leads

Battery Dimension Pictures



Item	Parameter (mm)
T	3.9
W	58
M	10
L	90
L_1	92
BL	92 ± 1
CL	100



1 YEAR WARRANTY

DNK





ANNOUNCEMENTS

- A LiPo Sack or metal/ceramic storage container is safest. Always store your LiPo's partially charged so they maintain their performance levels over time; there is no need to cycle them unless stored for periods longer than 3-6 months.
- LiPo batteries must only be charged with a manufacturer recommended LiPo charger.
- NEVER extinguish LiPo batteries with water.

CONTACT INFO

Mail: sales@dnkpower.com

Tel:+86 755 36827358 Hour of operation: 9:00am-6:00pm, Mon. to Fri.

Mob:+86 189 4877 2006 Learn More on: https://www.dnkpower.com/

Specifications are subject to change without notice.