



DNK

1 YEAR WARRANTY




Different Temperature Discharge Curve




Different Rate Charge Curve

Battery Dimension Pictures



Item	Parameter (mm)
T	4.5
W	12
M	8
L	20
L ₁	22
BL	22 ± 1
CL	100



Specifications are subject to change without notice.

3.7V DNK451220 95mAh LiPo Battery Pack with PCM. This datasheet describes the properties which is manufactured by DNK POWER Co. Ltd.- China

Electrical Data

Part Number	DNK451220
Nominal Voltage	3.7V
Nominal Capacity	95mAh
Internal Impedance	< 60mΩ
Charge Voltage	4.2V
Recommended Charge Current	0.2C
Allowed Max Charge Current	0.5C
Output Voltage Range	4.2 -2.5V
Recommend Discharge Current	0.2C
Max Continuous Discharge Current	1C
Pulse Discharge Current	3C(10mS)
Discharge Cut-off Voltage	2.5 ± 0.05V
Cycle Life to 80% Health	500(0.2C, 25°C)

Environmental Data

Charging Temperature Range	0 - 45°C
Discharge Temperature Range	-20 - 60°C
Storage Period 1 Week	-20 - 45°C
Storage Period 1 Month	-10 - 45°C
Storage Period 6 Months	0 - 35°C

Battery Protection

Over Charge	4.275 ± 50mV
Over Discharge	2.5 ± 50mV
Over Current	3A - 5A
Short Circuit	Yes

Mechanical Data

Dimension	22×12×4.5 mm
Weight	≤2g
Battery Terminals	WC/FL*

*WC=With Connector FL=Flying Leads

ANNOUNCEMENTS

- Don't use the unspecified charger;
- Don't reverse polarity (and terminal);
- Don't connect battery to the plug socket or car-cigarette-plug;
- Don't touch a leaked battery directly;
- Don't fall, hit, bent the batteries' body;
- Don't get into a microwave or a high pressure container;
- Keep the battery away from babies

CONTACT INFO

Mail: sales@dnkpower.com

USA Phone:(+1)302 202 0599

Tel:+86 755 36827358

Hour of operation: 9:00am-6:00pm, Mon. to Fri.

Mob:+86 189 4877 2006

Learn More on: <https://www.dnkpower.com/>