


1 YEAR WARRANTY


DNK

3.7V DNK601332 170mAh LiPo Battery Pack with PCM. This datasheet describes the properties which is manufactured by DNK POWER Co. Ltd.- China.

Battery Dimension Pictures



| Item | Parameter (mm) |
|----------------|----------------|
| T | 6 |
| W | 13 |
| M | 6 |
| L | 32 |
| L ₁ | 34 |
| BL | 34 ± 1 |
| CL | 100 |



Electrical Data

| | |
|----------------------------------|-----------------|
| Part Number | LP 601332 |
| Nominal Voltage | 3.7V |
| Nominal Capacity | 170 mAh |
| Internal Impedance | <60mΩ |
| Charge Voltage | 4.2V |
| Recommended Charge Current | 0.2C |
| Allowed Max Charge Current | 0.5C |
| Output Voltage Range | 4.2 - 2.5V |
| Recommend Discharge Current | 0.2C |
| Max Continuous Discharge Current | 1C |
| Pulse Discharge Current | 3C(10mS) |
| Discharge Cut-off Voltage | 2.5 ± 0.05V |
| Cycle Life to 80% Health | 500(0.2C, 25°C) |

Environmental Data

| | |
|-----------------------------|-------------|
| Charging Temperature Range | 0 - 45° C |
| Discharge Temperature Range | -20 - 60° C |
| Storage Period 1 Week | -20 - 45° C |
| Storage Period 1 Month | -10 - 45° C |
| Storage Period 6 Months | 0 - 35° C |


Battery Protection

| | |
|----------------|--------------|
| Over Charge | 4.275 ± 50mV |
| Over Discharge | 2.5V ± 50mV |
| Over Current | 3A to 5A |
| Short Circuit | Yes |

Mechanical Data

| | |
|--------------------------------|----------------|
| Dimension(L ₁ +W*T) | 34 x 13 x 6 mm |
| Weight | ≤5 g |
| Battery Terminals | WC/FL* |

*WC=With Connector FL=Flying Leads Specifications are subject to change without notice.



ANNOUNCEMENTS

- It is not permissible to mix old li-po batteries or half-used li-po batteries with new li-po batteries as this may result in over-discharge.
- LiPo batteries must only be charged with a manufacturer recommended LiPo charger.
- When charging LiPo batteries, they must be charged at the voltage of the number of cells in series. Example: A 5s4p pack must be charged as a 5 cell pack.

CONTACT INFO

Mail: sales@dnkpower.com
 Tel: +86 755 36827358
 Mob: +86 189 4877 2006
 Hour of operation: 9:00am-6:00pm, Mon. to Fri.
 Learn More on: <https://www.dnkpower.com/>