


1 YEAR WARRANTY


DNK

3.7V DNK702040 500mAh LiPo Battery Pack with PCM. This datasheet describes the properties which is manufactured by DNK POWER Co. Ltd.- China.

Battery Dimension Pictures



Item	Parameter (mm)
T	7.0
W	20
M	10
L	41
L ₁	43
BL	43 ± 1
CL	100



Electrical Data

Part Number	LP 702040
Nominal Voltage	3.7V
Nominal Capacity	500 mAh
Internal Impedance	<60mΩ
Charge Voltage	4.2V
Recommended Charge Current	0.2C
Allowed Max Charge Current	0.5C
Output Voltage Range	4.2 - 2.5V
Recommend Discharge Current	0.2C
Max Continuous Discharge Current	1C
Pulse Discharge Current	3C(10mS)
Discharge Cut-off Voltage	2.5 ± 0.05V
Cycle Life to 80% Health	500(0.2C, 25°C)

Environmental Data

Charging Temperature Range	0 - 45° C
Discharge Temperature Range	-20 - 60° C
Storage Period 1 Week	-20 - 45° C
Storage Period 1 Month	-10 - 45° C
Storage Period 6 Months	0 - 35° C


Battery Protection

Over Charge	4.275 ± 50mV
Over Discharge	2.5V ± 50mV
Over Current	3A to 5A
Short Circuit	Yes

Mechanical Data

Dimension(L ₁ +W*T)	43 x 20 x 7.0 mm
Weight	appr 8.4 g
Battery Terminals	WC/FL*

*WC=With Connector FL=Flying Leads Specifications are subject to change without notice.



ANNOUNCEMENTS

- It is not permissible to mix old li-po batteries or half-used li-po batteries with new li-po batteries as this may result in over-discharge.
- LiPo batteries must only be charged with a manufacturer recommended LiPo charger.
- When charging LiPo batteries, they must be charged at the voltage of the number of cells in series. Example: A 5s4p pack must be charged as a 5 cell pack.

CONTACT INFO

Mail: sales@dnkpower.com
 Tel: +86 755 36827358
 Hour of operation: 9:00am-6:00pm, Mon. to Fri.
 Mob: +86 189 4877 2006
 Learn More on: <https://www.dnkpower.com/>