

3.7V DNK725888 5000mAh LiPo Battery Pack with PCM. This datasheet describes the properties which is manufactured by DNK POWER Co. Ltd.- China.


1 YEAR WARRANTY

DNK

Battery Dimension Pictures



Item	Parameter (mm)
T	7.2
W	58
M	10
L	89
L ₁	91
BL	91 ± 1
CL	100



Electrical Data

Part Number	LP 725888
Nominal Voltage	3.7V
Nominal Capacity	5000 mAh
Internal Impedance	<60mΩ
Charge Voltage	4.2V
Recommended Charge Current	0.2C
Allowed Max Charge Current	0.5C
Output Voltage Range	4.2 - 2.5V
Recommend Discharge Current	0.2C
Max Continuous Discharge Current	1C
Pulse Discharge Current	3C(10mS)
Discharge Cut-off Voltage	2.5 ± 0.05V
Cycle Life to 80% Health	500(0.2C, 25°C)

Environmental Data

Charging Temperature Range	0 - 45° C
Discharge Temperature Range	-20 - 60° C
Storage Period 1 Week	-20 - 45° C
Storage Period 1 Month	-10 - 45° C
Storage Period 6 Months	0 - 35° C


Battery Protection

Over Charge	4.275 ± 50mV
Over Discharge	2.5V ± 50mV
Over Current	3A to 5A
Short Circuit	Yes

Mechanical Data

Dimension(L ₁ +W*T)	91 x 58 x 7.2 mm
Weight	appr 83.4 g
Battery Terminals	WC/FL*

*WC=With Connector FL=Flying Leads Specifications are subject to change without notice



ANNOUNCEMENTS

- LiPo batteries must only be charged with a manufacturer recommended LiPo charger.
- LiPo batteries have very specific charging requirements. Some chargers, such as those used for toys or cell phones, are made to charge a specific cell count and are not configurable for other cell counts. The LiPo charger used must be able to handle the cell count of the battery you are charging.

CONTACT INFO

Mail: sales@dnkpower.com
 Tel:+86 755 36827358
 Mob:+86 189 4877 2006
 Hour of operation: 9:00am-6:00pm, Mon. to Fri.
 Learn More on: <https://www.dnkpower.com/>